

Functionality Assessment of Household Tap Connection under National Jal Jeevan Mission - 2022



District Report: Bemetara, Chhattisgarh Survey Duration: February to April 2022

Contents

Ab	orev	iations	3
Glo	ssa	ry	4
1.	Fa	actsheet	6
2.	Co	ontext	8
2.1		District snapshot: Bemetara	8
2.2		FHTC Assessment Objectives	9
2.3		Assessment Methodology	9
2.4	٠.	Sample Size	9
2.5		Sampling Methodology	10
2.6		Methodology for Water Quantity Measurement at Households	11
2.7		Methodology for Water Quality Measurement	11
2.8		Project implementation	12
2.9	١.	Sample coverage	13
2.1	0.	Sampled village and household profile	13
3.	Fi	ndings	14
3.1		Functionality status of FHTC at household level	14
3.2		Quantity, Regularity, and Quality of Water	15
3.3		Average water supply days in a week	18
3.4		Household utilization of water for drinking and other activities	18
3.5		Status at HH level (Nh=397)	18
3.6		Source sustainability at the village level	19
3.7	•	Water quality monitoring and surveillance in the villages	20
3.8		Status of JJM	20
3.9	١.	Perception of HHs on Outcome Indicators	21
3.1	0.	User satisfaction	22
4.	Ar	nnexures	23
2	1.1.	Summary of villages	23
2	1.2.	Functionality – 55 LPCD vs regularity vs potability vs working tap connection	23
4	1.3.	Villages not meeting the quality parameters	24

Abbreviations

7 1007 0 7 1011 0 1 10	
AWC	Aanganwadi Centre
FHTC	Functional Household Tap Connection
Gol	Government of India
GP	Gram Panchayat
HF	Health Facility
HH	Household
HGJ	Har Ghar Jal
JJM	Jal Jeevan Mission
LPCD	Litres per Capita per Day
MVS	Multi-village Scheme
NJJM	National Jal Jeevan Mission
RC	Residual Chlorine
O&M	Operation and Maintenance
OHT	Over Head Tank
PSU	Primary Sampling Unit
PWS	Piped Water Supply
SVS	Single Village Scheme
VAP	Village Action Plan
VWSC	Village Water and Sanitation Committee
WQMIS	Water Quality Monitoring and Information System

Glossary

- 1. **Community** Group of people living in one particular area or village/habitation
- 2. **Cross-sectional research** A cross-sectional study is a type of research design in which data is collected from a relatively large and diverse group of people at a single point in time
- 3. **Drinking water source** Groundwater (open well, borewell, tube well, handpump, spring, etc.)/ surface water (river, lake, pond, reservoir, etc.)/rainwater, available for drinking and domestic use
- 4. Improved sources The following sources as considered improved by the National Family Health Survey definitions: Piped water into dwelling, yard/plot with a tap, piped water connected to public stand-posts, tube well or borewell, Hand pump, dug well– protected, Spring–protected, Rainwater, Water ATM/ Community RO plant/ Community Water Purification Plant (CWPP)
- 5. **Unimproved sources** The following sources as considered unimproved by the National Family Health Survey definitions: Unprotected spring, unprotected dug well, cart with small tank / drum, Tanker/ truck, Surface water (river/ dam/ lake/ pond/ canal), and bottled water
- 6. **Functional Household Tap Connection (FHTC)** A tap connection to a rural household for providing drinking water in adequate quantity of prescribed quality on regular basis.
- 7. **Functionality of FHTC** Functionality of a tap connection is defined as having infrastructure, i.e., household tap connection providing water in adequate quantity, as presented:

Definitions	Fully-functional	Partially-functional	Non-functional
Quantity	>= 55 LPCD	> 40 lpcd - < 55 LPCD	< 40 LPCD
Regularity	12 months or daily basis	9-12 months or < daily basis	< 9 months or < daily basis
Quality	Potable	Potable	Non potable

- 8. **Quantity (in litres)** of water received by households per person per day should meet the service level of 55 LPCD
- 9. **Functionality Assessment** An assessment of the functionality of rural household tap connections based on a sample survey
- **10. Fully Regular –** Regularity of water is considered when a rural household receives water for 12 months on daily basis or as per schedule."
- 11. **Potability –** Potable water is water that is safe to be used as drinking water. Parameters of potable water are mentioned below:

Parameters for potable water tested in the survey		Unit	Acceptable Limit	Permissible Limit in the absence of alternative sources
i.	pH (tested on site)	-	6.5 to 8.5	No relaxation
ii.	Free residual chlorine (tested on site)	Mg/litre	0.2	1
iii.	Turbidity	NTU	1	5
iv.	Total hardness	Mg/litre	200	600
٧.	Total alkalinity	Mg/litre	200	600
vi.	Chloride	Mg/litre	250	1000
vii.	Ammonia	Mg/litre	0.5	No relaxation
viii.	Phosphate	Mg/litre	0.3	1
ix.	Iron (in hotspots only)	Mg/litre	1	No relaxation
X.	Nitrate	Mg/litre	45	No relaxation
xi.	Sulphate	Mg/litre	200	400
xii.	Total dissolved solids	Mg/litre	500	2000
xiii.	Fluoride	Mg/litre	1	1.5

xiv.	Arsenic (in hotspots only)	Mg/litre	0.01	No relaxation	
XV.					
			Shall not be detectable in any 100 ml sample	any 100 ml sample	
	coliform bacteria				

- 12. **Sampling** Selection of a subset of individuals from within a statistical population to estimate water service delivery among the population. In the current study, households have been sampled to estimate the representation of the village and subsequently of the district as well as of the state.
- 13. Types of schemes: Following are the piped water supply schemes that were assessed
 - a. Mini-solar based piped water supply scheme in isolated/tribal hamlets
 - b. Single Village Scheme (SVS) in villages having adequate groundwater that needs treatment
 - c. Single village scheme (having adequate groundwater/ spring water/ local or surface water source of prescribed Quality)
 - Retrofitting of ongoing schemes taken up under erstwhile NRDWP for the last mile connectivity/ retrofitting of completed rural water supply schemes to make it JJM compliant
 - e. Multi-village PWS scheme with water grids/ regional water supply schemes
- 14. Village Action Plan (VAP) Plan prepared by Gram Panchayat and/ or its sub-committee, i.e., VWSC/ Paani Samiti/ User Group, etc. based on baseline survey, resource mapping and felt needs of the village community to provide FHTC to every rural household, treat the generated greywater and plan its reuse, undertake surveillance activities, etc. VAP also indicates the fund requirement and timelines for completion of work under the Mission and will be approved by the Gram Sabha. Irrespective of the source of funding, all drinking water-related works in the village are taken up based on the VAP.
- 15. **Source Sustainability** includes measures such as aquifer recharge, rainwater harvesting, increased storage capacity of water bodies, reservoirs, de-silting, etc. improve the lifespan of water supply systems
- 16. **Har Ghar Jal (HGJ)** An administrative unit wherein all HHs are provided with water supply through FHTCs is called "Har Ghar Jal".
- 17. **Public Institutions** The public institutions in the survey include Aanganwadi Centre (AWC), Health Facilities, Schools, Gram Panchayat, and government buildings.
- 18. **Working tap connection –** A tap connection supplied water at least one day in the week, preceding of survey
- **19. Functional Scheme –** A scheme is said to be functional if it was reported to be working for all 12 months in a year.

1. Factsheet

Table 1: District level factsheet

Indicators	Chhattisgarh	Bemetara
Functionality status of FHTC at households		
Households (HHs) which received water through FHTC at	55	100
least once in last 7 days (%)		100
Fully functional (%)	71	45
Partially functional (%)	22	48
Non-functional (%)	7	7
Quantity of water received by households		
Adequate quantity (>55 LPCD) (%)	89	91
Partially adequate quantity (> 40 LPCD - < 55 LPCD) (%)	5	5
Inadequate quantity (<40 LPCD) (%)	6	4
Regularity of water received by households		
Fully Regular Supply (as per schedule) (%)	85	84
Partially Regular Supply (not as per schedule) (%)	10	8
Irregular Supply (less than 9 months' supply) (%)	5	8
Potable (Quality) water received by households		
Potable (%)	89	61
Non-potable (%)	11	39
Residual Chlorine (RCL) detected with in permissible limits (%)	33	21

Household level indicators		
Households receiving water supply daily-7 days a week (%)	90	100
Daily HH requirement of water being met by FHTC (%)	74	94
Households reported FHTC as a primary source of drinking water (%)	24	90
Households purifying water before drinking (%)	65	55
Households paying water service delivery charges (%)	40	10
Households having coping mechanisms during scarcity (%)	67	60
Households aware of grievance redressal mechanism for reporting problems with FHTC (%)	66	29
Households reported incidence of water-borne diseases in the last year (%)	0	0
Households reported a reduction in time and effort in collecting water (%)	73	97
Overall user satisfaction at the household level		
Regularity (%)	74	98
Overall quality (%)	74	96

Indicators	Chhattisgarh	Bemetara
Village level indicators (based on village questionnaire)		
Schemes reported to be functional (%)	40	56
Villages with groundwater resource (%)	66	75
Villages having groundwater recharge structure ¹ (%)	36	19
Water supply and storage status in villages		
Average no. of times water is supplied in a day	1	1
Villages having OHT/ Sump for storage of water (%)	47	62
Water quality monitoring and surveillance in the villages		
Villages with Field Test Kits (%)	20	44
Villages in which bacteriological test was done in last 1 year by VWSC/ Pani Samiti (%)	8	0
Villages reported to have a mechanism for chlorination (%)	3	19
VWSC/Pani Samiti and PWS signage in villages		
Village reported having presence of VWSC/ Pani Samiti (%)	24	6
Villages in which VWSC/ Pani Samiti is responsible for Operation & Maintenance of PWS schemes (%)	4	0
Villages in which persons are trained to use Field Test Kits (%)	20	38
Villages in which signages about JJM were observed (%)	2	0
Operation and maintenance at village		
Villages levying water service delivery to households (%)	32	19
Convergence of JJM activities with other schemes in the villages (%)	2	0
Villages having skilled manpower for Operation & Maintenance of PWS schemes (%)	17	0
Community monitoring of water wastage in villages (%)	9	6

 $^{^{1}}$ Out of villages who reported to have groundwater source (N $_{v}$ =12)




7

2. Context

Jal Jeevan Mission (JJM) was launched on the 15th of August 2019 with the objective to provide functional household tap connections (FHTCs) to all rural households.

Figure 1: Har Ghar Jal - Objective, Vision, & Outcome



In accordance with the overall objectives as specified in the Operational Guidelines for the implementation of the NJJM, GoI carried out a sample survey to assess the functionality of household tap connections. As part of this endeavour, NJJM, GoI engaged HTA Kantar Public to conduct the 'Functionality Assessment' of the household as well as public institution/buildings such as schools, anganwadis, gram panchayat buildings, public health facilities, and wellness centers in all the rural districts for the fiscal year 2021-22.

2.1. District snapshot: Bemetara

District Bemetara of Chhattisgarh has a population of 8,63,080. The district has 4 blocks. Out of 689 villages in the district, 133 are SC dominated and 10 are ST dominated villages. The district lies in Eastern Plateau and Hill Region and receives an annual rainfall of 1,380.9mm.

Presented here are district level information collated from the DDWS-IMIS:

Figure 2: District IMIS Status & Map

IMIS status:

- 13 (2% of all) villages are Har Ghar Jal
- 676 (98% of all) villages are Non-Har Ghar Jal
- Non-SC/ST dominated district
- Non-JE/AES
- No- History of water contamination
- 306 (44% of all) villages with PWS more than 20 FHTC



2.2. FHTC Assessment Objectives

Figure 3: Objectives of Functionality of Tap Connections



2.3. Assessment Methodology

A cross-section research design has been used for this functionality assessment study. Quantitative data were collected from villages and households across all states/UTs using the CAPI (Computer Assisted Personal Interviewing) mode. The survey includes two components, village, and household.

Figure 4: Survey Components & Respondents



2.4. Sample Size

The sample size was calculated to provide estimates with a 95% confidence interval (CI) and 5% margin of error (MoE) after incorporating the correction factor for a finite population considering the total number of geographic units having FHTCs.

- Village sample is estimated to be representative at the state level
- HH sample estimated to be representative at the district level



- Number of Har Ghar Jal (HGJ) villages were proportionately sampled at the district level
- All PWS schemes (up to 4) were covered per village. Per scheme approximately 9 (3 each from the head, middle, and tail HHs) or 18 households (6 each from head, middle, and tail HHs) were sampled to achieve the desired sample at the district level.


2.5. Sampling Methodology

As per the design, all villages having a PWS scheme with 20 or more functional household tap connections were included in the sample frame. The probability proportionate to size (PPS) method was used for village selection in each district. The steps for random selection of villages using PPS are as presented:

Figure 5: Steps for Village Sampling




The key considerations for the village and household sampling were:



The record of all district-wise village replacements is maintained and reported as part of the annexure.

2.6. Methodology for Water Quantity Measurement at Households

Figure 7: Steps for Measuring Flowrate from Supply-tap at HHs



The flow rate of the water supply was measured using a container with gradual markings (either 5 litres or 1 litre, based on the flow of the tap) and a stopwatch/timer-watch. The process followed is as described in Figure 7.

In the case of households where the FHTC is connected directly with the storage tank, the following steps were adopted to measure the quantity:


- Assessor first asked and recorded length, breadth, and height.
- Assessor dipped a 5 feet long rod, marked the level of the water table, and calculated the volume – length x breadth x-height of water.
- Next the assessor opened the valve of the connection and allowed the water to flow inside the storage for 10 minutes.
- After 10 mins, the valve was closed, and the assessor again dipped the rod and recorded the new height of the water inside the tank. Based on this new 'height' and the CAPI calculated the changed volume.
- The difference in the volume of water in 10 minutes divided by 10 provided the flow rate of the water supply per minute.

The water flow rate was not measured for village-level public institutions.

2.7. Methodology for Water Quality Measurement

Water quality was tested for all public institutions available in the villages, including schools, anganwadis, gram panchayat buildings, public health facilities, and wellness centres, and at the selected households. Two types of quality tests were carried out – a) spot test for pH and free residual chlorine, and b) water sample was collected and transported to labs for testing against 13 quality parameters (total 15) as specified in Figure 8.


Figure 8: On-site & Laboratory Based Quality Test



JJM, with the support of the BMI Division of ICMR, enabled a new interface on the WQMIS portal for "Functionality Assessment (FA) User" to enable seamless harmonization of water sample registration, sample submission for testing, and sharing of results as per the applicable quality parameters.

2.8. Project implementation

An overview of the project implementation is as presented:



A total of 8 teams (comprising 8 supervisors, 48 assessors, and 8 water collection assistants) were recruited, trained, and deployed to complete the survey across the state of Chhattisgarh. One survey team covered approximately 2 – 3 districts. The state-wise team deployment and fieldwork dates were as presented:

Table No. 1:	: State-wise team deployment and data collection start & end dates				
State		Teams deployed	Start date	End date	Total data collection days
Chhattisgarh		8 Teams	2/28/2022	4/20/2022	50 Days

A four-tier quality control (QC) system was put in place. At the ground level, the data collection exercise was done using a computer-aided Personal Interview (CAPI) application which contained all logic and skip-checks inbuilt. Also, 5% of the total samples were accompanied by the supervisors. Sub-targeted QC was done by the state field managers (5%) and the central project management team (5%). Apart from this, the central research team monitored the data trend and as per requirement debriefed data collection teams to improve quality.

2.9. Sample coverage

Table No. 2:	Sample covered				
	Targete	d sample		Achieved sam	ple
District	Village	НН	Village	НН	Public Institutions
Bemetara	16	396	16	397	28
Chhattisgarh	383	10,611	383	10,711	312

2.10. Sampled village and household profile


SAMPLED VILLAGES SAMPLED HOUSEHOLDS Total no. of villages covered in the district - 16 Total no. of households covered in the district Percentage of SC dominated villages covered in the district is 6% (which is lower than the Proportion of General - 7%, SC 10%, ST% 2, state average, i.e., 8%) OBC 81% households Percentage of ST dominated villages covered 46% of the FHTC connections are under the in the district is 0% (which is lower than the name of a female member state average, i.e., 54%) Average household size - 7 Higher proportion of **pump operator** >75% positive user experience in 5/5 interviewed at the village level measures No, the district reported to have any historical incidence of water contamination

3. Findings

3.1. Functionality status of FHTC at household level

A. Overall Functionality* (in %)

Figure 10: Functionality of HH tap connection



It has been found that 100 percent of the sampled HHs (N=397) had working tap connections (i.e., received water at least once in last 7 days). Less than half out of ten (45percent) HHs had fully functional tap connection (i.e., HHs receiving adequate quantity of prescribed quality of water on a regular basis).


3.2. Quantity, Regularity, and Quality of Water

Under JJM, functionality is defined as having infrastructure, i.e., household tap connection providing water in adequate quantity (55 LPCD or more) of prescribed quality on regular basis (every day or as decided by GP and/ or its sub-committee) with adequate pressure. It will also include long-term source and system sustainability. Presented here are the findings in this respect.

A. Water quantity measured as LPCD (Litres per Capita per Day)


91% HHs reported receiving adequate quantity of water

Figure 11: Quantity of water received by households



Quantity of water received across head, middle, and tail end HHs


Figure 12: Quantity of water received across head, middle and tail end households



B. Regularity of water supply to households


84% HHs receive a regular supply of water (as per agreed schedule)

Figure 13: Regularity of water received by households




Regularity of water received across head, middle, and tail end

Figure 13: Regularity of water received across head, middle and tail end households



C. Water quality - Potability

Figure 14: Potable water received by households



 $N_h = 397$

Table No. 3: Village quality parameters reported within permissible range (% sample within permissible range)

Quality Parameters (N _v =16)	Water Samples Tested from Public Institutes			
	Anganwadi	Health	Schools	Others
	Centre	Facility		
pH (on-site)	100		100	100
Turbidity	100		100	100
Total Hardness	30		50	17
Total Alkalinity	90		100	100
Chloride	100		100	100
Ammonia	Not tested			
Iron	No history			
Nitrate	Not tested			
Sulphate		Not t	ested	
Total Dissolved Solids	100		100	100
Bacteriological Test	100		100	100
Fluoride	No history			
Arsenic		No hi	istory	

^{*}Potable water has been considered basis testing of water samples through laboratory tests for physical, chemical, and bacteriological as given in Table 4 parameters (within acceptable/permissible range) and onsite testing of pH. The details of laboratory test are mentioned in the table given above in the glossary.

 Table No. 4:
 Household water quality parameters reported within permissible range

(in % sample within permissible range)

Quality Parameters	No of water samples tested	% Samples within permissible range	
pH (on-site)	397	100	
Turbidity	375	100	
Total Hardness	372	59	
Total Alkalinity	371	99	
Chloride	369	100	
Ammonia	Not tes	sted	
Iron	No his	tory	
Nitrate	Not tes	sted	
Sulphate	Not tes	sted	
Total Dissolved Solids	373	100	
Bacteriological Test (Absence)	350	100	
Fluoride	tory		
Arsenic	tory		

Safeguarding piped water supply for unforeseen bacteriological contamination-Presence of Residual Chlorine (RC)

The Residual Chlorine (RC) in the Bemetara district was found in 21% samples. Out of which 1% samples were having RC outside range whereas 71% samples, had no RC. It may be mentioned that 100% of water samples passed the bacteriological contamination test but to assure the protection against bacteriological contamination, addition of RC is must in PWS system.

The Residual Chlorine in piped water supply is one of the most important preventive actions to assure quality of water against bacteriological contamination from source to consumption. The presence of residual chlorine within permissible limits is indicator of well-maintained and healthy piped water supply system.

It is advised that behavioural change communication campaigns on appropriate dosage of residual chlorine is held in all villages and monitoring system for chlorine dosing is established. The FTK must have residual chlorine testing facility for effective WQM&S.


Comment on functioning of District Lab:

The district lab tested water samples for 6 water quality parameters. 425 water samples were submitted, and 421 water samples were tested, and reports made available. The turnaround time for testing was more than 48 hours in most cases.

The labs did not have any issue with testing the number of water samples submitted nor had any issues with human resources, reagents, etc. However, the only concern was the lab did not accept any samples during weekends and public holidays.

3.3. Average water supply days in a week

Figure 15: Average number of days households receive water supply in a week (in %)




3.4. Household utilization of water for drinking and other activities

Fulfilment of requirement


94% HHs reported that their daily requirement of water is being met by FHTCs

Figure 17: Daily household's requirement of water being met by FHTC





Primary source of drinking water 90% HHs reported HH tap connection as their primary source of drinking water


Figure 18: Daily household's requirement of water being met by drinking water




3.5. Status at HH level (Nh=397)










% HH aware of grievance redressal mechanism for reporting problems with FHTC








^{*}HHs who reported complaints in last 1 year

3.6. Source sustainability at the village level

Schemes based on surface and ground water

29% of schemes are reported to be based on surface water and 53% ground water.

Figure 19: Schemes based on water source in village




^{*&#}x27;Surface Water Source' is Stream, Spring, Glacier, River, lake, pond etc. and Groundwater Source is open well, borewell, tube well, handpump, spring, etc

Villages reported having presence of a groundwater source

75% of villages reported the presence of groundwater sources like improved dug wells and borewells, and were supported by recharging structures.

Figure 20: Villages reported the presence of groundwater sources and among those how many reported to have a recharge structure




The top 3 other source sustainability measure taken by villages

Figure 21: Villages reported having taken other source sustainability measure



3.7. Water quality monitoring and surveillance in the villages

Figure 22: Water quality monitoring and surveillance by villages



3.8. Status of JJM

A. VWSC/Pani Samiti and PWS signage in villages (N_v=16)

Presence of VWSC/Pani Samiti	VWSC/Pani Samiti responsible for O&M of PWS Schemes	% Villages – VWSC/PO trained to use FTKs	% Villages in which signages about JJM was observed	
6%	0%	38%	0%	

B. Water supply, storage and operation & maintenance at village level (N_v=16)

Average no. of supply in a day	% Villages levying water service delivery to HH	% Villages having skilled manpower for O&M for PWS	Community monitoring of water wastage in villages	
1	19%	0%		
% Villages having OHT/ Sump	% Villages with O&M challenges	Primary points for reporting grievances	Key problems for reporting grievances	
62%	0%	Helpline	Pipeline leakage	


3.9. Perception of HHs on Outcome Indicators

a. Health Incidence of water borne diseases at HH level in last one year as reported Figure 23: Household reported incidence of water borne diseases in last one year 100 80 60 40 20 0 Waterborne Water related None diseases ■ % of HH

diseases

b. Economic Income Change in employment days since FHTC programmers/schemes


Figure 24: Household reported a change in employment days since FHTC programmes /schemes



c. Drudgery Reduction in time and effort in collecting water

N_h=397

Figure 25: Households reported reduction in time and effort in collecting water



3.10. User satisfaction

Table No. 5: User satisfaction - more than 75% happy with FHTC services					
S. No.	Parameter (N _h =397) In %				
1	Regularity	<u>•</u> •	98		
2	Overall quality	00	96		
3	Colour	<u>•</u> •	97		
4	Taste	00	98		
5	Odour	<u></u>	98		

Note:

Base (N_v)=16 means all villages sampled and covered in Bemetara district

Base (N_H)=397 means all households sampled and covered across the 16 villages in Bemetara district

Base (N_H)=397 means all households where female members used to fetch water before HH tap connection

4. Annexures

4.1. Summary of villages

Table No. 6: Village summary						
S.No.	Name of sample village	Sample HHs	Actual sample HHs (achieved)	No. of scheme	No of source of surface water available in the village	No of source of ground water available in the village
#	Total	396	413	21	14	30
1	Junadandu	18	19	1	1	
2	Chicholi	18	19	2		1
3	Temari	18	19	2	10	5
4	Murra	18	19	2		3
5	Dhara	18	19	1	1	
6	Mau	18	19	1		3
7	Semariya	36	37	1		5
8	Khandsara	36	37	1	1	
9	Basin	36	37	1		5
10	Kurud	18	19	2		1
11	Raudra	36	37	1		
12	Patarjhoti	36	37	2	1	1
13	Harduwa	18	19	1		2
14	Bhimbhori	36	37	1		1
15	Sarholi	18	19	1		2
16	Lenjwara	18	20	1		1

4.2. Functionality – 55 LPCD vs regularity vs potability vs working tap connection

Table No. 7: Functionality of HH tap connection						
S. No.	Village	Fully Functional*	Adequate Quantity (% HH)	Fully Regular Supply (% HH)	Potable (Quality) (% HH)	Working tap connections (%HH)
#	Total	45	91	84	62	100
1	Junadandu	0	100	100	0	100
2	Chicholi	0	100	56	6	100
3	Temari	0	100	61	0	100
4	Murra	22	100	100	22	100
5	Dhara	28	61	100	56	100
6	Mau	89	100	100	89	100
7	Semariya	44	69	72	100	100
8	Khandsara	78	89	100	89	100
9	Basin	92	100	94	97	100
10	Kurud	50	100	100	50	100
11	Raudra	53	67	72	100	100
12	Patarjhoti	64	100	75	89	100
13	Harduwa	44	100	94	44	100
14	Bhimbhori	3	100	81	14	100
15	Sarholi	72	89	83	100	100
16	Lenjwara	11	100	68	11	100

^{*} Fully Functional has been computed as = Adequate Quantity ∩ Fully Regularity Supply ∩ Potable (Quality)



4.3. Villages not meeting the quality parameters

1. pH	/A = = = - 1 : 1 1	parameters dissatis	fied at village	level	
S.No.	Block	Range- 6.5 to 8.5) Panchayat Name	Villages	No. of HHs outside the acceptab	le range
NA	Name NA	NA	NA	NA	
		lorine (Acceptable I		* ** *	
S.No.	Block Name	Panchayat Name	Villages	HHs outside the acceptable/permissible range	HHs with no chlorine
1	Bemetara	Dhara	Dhara	0	9
2		Khandsara	Khandsara	0	27
3		Mau	Mau	0	18
4		Semariya	Semariya	0	36
5	Berla	Bhimbhouri	Bhimbhori	0	28
6		Lengwara	Lenjwara	0	19
7		Surholi	Sarholi	0	9
8	Nawagarh	Chicholi	Chicholi	0	18
9		Junadandu	Junadandu	0	6
10 11		Murra Temri	Murra Temari	0	18 14
12	Saja	Budhwara	Basin	0	27
13	Saja	Harduwa	Harduwa	0	18
14		Kurud	Kurud	0	17
15		Patarjhori	Patarihoti	1	24
16		Roudra	Raudra	3	23
	rbidity (Acce	ptable Range- 1 to 5		-	
S.No.	Block Name	Panchayat Name	Villages	HHs outside the acceptable/permis	sible range
1	Nawagarh	Murra	Murra		1
4. To		(Acceptable Range-	200 to 600 Mi	lligram/litre)	
S.No.	Block Name	Panchayat Name	Villages	HHs outside the acceptable/permiss	ible range
1	Bemetara	Dhara	Dhara		8
2		Khandsara	Khandsara		4
3		Mau	Mau		2
4	Berla	Bhimbhouri	Bhimbhori		31
5		Lengwara	Lenjwara		17
6	Nawagarh	Chicholi	Chicholi Junadandu		17
7		Junadandu	umadandil		
		Murro			18
8		Murra Temri	Murra		18 14
9	Saia	Temri	Murra Temari		18 14 18
9 10	Saja	Temri Budhwara	Murra Temari Basin		18 14 18 1
9 10 11	Saja	Temri Budhwara Harduwa	Murra Temari Basin Harduwa		18 14 18 1 10
9 10 11 12	Saja	Temri Budhwara Harduwa Kurud	Murra Temari Basin Harduwa Kurud		18 14 18 1 10 9
9 10 11 12 13	·	Temri Budhwara Harduwa Kurud Patarjhori	Murra Temari Basin Harduwa Kurud Patarjhoti	ligram/litre)	18 14 18 1 10 9
9 10 11 12 13	·	Temri Budhwara Harduwa Kurud	Murra Temari Basin Harduwa Kurud Patarjhoti	ligram/litre) HHs outside the acceptable/permiss	18 14 18 1 10 9 4
9 10 11 12 13 5. To	tal alkalinity (Temri Budhwara Harduwa Kurud Patarjhori Acceptable Range-	Murra Temari Basin Harduwa Kurud Patarjhoti 200 to 600 Mil		18 14 18 1 10 9 4
9 10 11 12 13 5. To S.No .	tal alkalinity (Block Name	Temri Budhwara Harduwa Kurud Patarjhori Acceptable Range- Panchayat Name	Murra Temari Basin Harduwa Kurud Patarjhoti 200 to 600 Mil Villages		18 14 18 1 10 9 4
9 10 11 12 13 5. To S.No .	tal alkalinity (Block Name Berla Nawagarh	Temri Budhwara Harduwa Kurud Patarjhori Acceptable Range- Panchayat Name Bhimbhouri	Murra Temari Basin Harduwa Kurud Patarjhoti 200 to 600 Mil Villages Bhimbhori Junadandu	HHs outside the acceptable/permiss	18 14 18 1 10 9 4 ible range
9 10 11 12 13 5. To S.No .	tal alkalinity (Block Name Berla Nawagarh	Temri Budhwara Harduwa Kurud Patarjhori Acceptable Range- Panchayat Name Bhimbhouri Junadandu	Murra Temari Basin Harduwa Kurud Patarjhoti 200 to 600 Mil Villages Bhimbhori Junadandu	HHs outside the acceptable/permiss	18 14 18 1 10 9 4 ible range
9 10 11 12 13 5. To S.No. 1 2 6. Ch S.No.	tal alkalinity (Block Name Berla Nawagarh lloride (Accep Block Name NA	Temri Budhwara Harduwa Kurud Patarjhori Acceptable Range- Panchayat Name Bhimbhouri Junadandu otable Range- 250 to Panchayat Name	Murra Temari Basin Harduwa Kurud Patarjhoti 200 to 600 Mil Villages Bhimbhori Junadandu 1000 Milligrar Villages	HHs outside the acceptable/permiss	18 14 18 1 10 9 4 ible range
9 10 11 12 13 5. To S.No. 1 2 6. Ch S.No.	tal alkalinity (Block Name Berla Nawagarh lloride (Accep Block Name NA	Temri Budhwara Harduwa Kurud Patarjhori Acceptable Range- Panchayat Name Bhimbhouri Junadandu otable Range- 250 to Panchayat Name	Murra Temari Basin Harduwa Kurud Patarjhoti 200 to 600 Mil Villages Bhimbhori Junadandu 1000 Milligrar Villages	HHs outside the acceptable/permiss m/litre) HHs outside the acceptable/permiss	18 14 18 1 10 9 4 ible range
9 10 11 12 13 5. To S.No. 1 2 6. Ch S.No.	tal alkalinity (Block Name Berla Nawagarh loride (Accept Block Name NA nmonia (Accept Block Name	Temri Budhwara Harduwa Kurud Patarjhori Acceptable Range- Panchayat Name Bhimbhouri Junadandu btable Range- 250 to Panchayat Name NA ptable Range- 0.5 M Panchayat Name	Murra Temari Basin Harduwa Kurud Patarjhoti 200 to 600 Mil Villages Bhimbhori Junadandu 1000 Milligrat Villages NA illigram/litre) Villages	HHs outside the acceptable/permiss m/litre) HHs outside the acceptable/permiss	18 14 18 1 10 9 4 ible range
9 10 11 12 13 5. To S.No. 1 2 6. Ch S.No. NA 7. An S.No.	tal alkalinity (Block Name Berla Nawagarh loride (Accer Block Name NA nmonia (Accer Block Name	Temri Budhwara Harduwa Kurud Patarjhori Acceptable Range- Panchayat Name Bhimbhouri Junadandu otable Range- 250 to Panchayat Name NA ptable Range- 0.5 M	Murra Temari Basin Harduwa Kurud Patarjhoti 200 to 600 Mil Villages Bhimbhori Junadandu 1000 Milligrat Villages NA illigram/litre) Villages	HHs outside the acceptable/permiss m/litre) HHs outside the acceptable/permiss NA	18 14 18 1 10 9 4 ible range



S.No.	Block Name	Panchayat Name	Villages	HHs outside the acceptable/permissible range				
NA	NA	NA	NA	NA				
9. Nitr	9. Nitrate (Acceptable Range- 1 Milligram/litre)							
S.No.	Block Name	Panchayat Name	Villages	HHs outside the acceptable/permissible range				
NA	NA	NA	NA	NA				
10. St	Ilphate (Accer	otable Range- 200 to	400 Milligran	n/litre)				
S.No.	Block Name	Panchayat Name	Villages	HHs outside the acceptable/permissible range				
NA	NA	NA	NA	NA				
11. To	tal dissolved	solids (Acceptable I	Range- 500 to	2000 Milligram/litre)				
S.No.	Block Name	Panchayat Name	Villages	HHs outside the acceptable/permissible range				
1	Nawagarh	Murra	Murra	1				
12. Ba	acteriological	test (Presence)						
S.No.	Block Name	Panchayat Name	Villages	HHs outside the acceptable/permissible range				
1	Nawagarh	Junadandu	Junadandu	1				
13. Flu	uoride (Accep	table Range- 1 to 1.	5 Milligram /li	tre)				
S.No.	Block Name	Panchayat Name	Villages	HHs outside the acceptable/permissible range				
1	Saja	Harduwa	Harduwa	1				
14. Ar	14. Arsenic (in hotspots) (Acceptable Range- 0.01 Milligram /litre)							
S.No.	Block Name	Panchayat Name	Villages	HHs outside the acceptable/permissible range				
NA	NA	NA	NA	NA				