

Functionality Assessment of Household Tap Connection under National Jal Jeevan Mission - 2022



District Report: Shivamogga, Karnataka Survey Duration: February to April 2022

Ab	brevia	tions
Gl	ossary	4
1.	Con	text
2.	Dist	rict snapshot:
3.	FHT	C Assessment Objectives9
4.		essment Methodology9
	4.1.	Sample Size
4	4.2.	Sampling Methodology10
	4.3.	Methodology for Water Quantity Measurement at Households
	4.4.	Methodology for Water Quality Measurement
	4.5.	Project implementation
4	4.6.	Sample coverage
	4.7.	Sampled village and household profile13
ł		ndings14
	5.1	Quantity, Regularity, and Quality of Water14
	5.2	Functionality status of FHTC14
	5.3	Average water supply days in a week17
	5.4	Household utilization of water for drinking and other activities18
	5.5	Source sustainability at the village level19
	5.6	Water quality management
	5.7	Status of JJM20
	5.8	Perception of HHs on Outcome Indicators21
	5.9	User satisfaction22
6	Ann	exures
(6.1.	Summary of villages23
(6.2.	Functionality – 55 LPCD vs regularity vs potability vs working tap connection23
(6.3.	Villages not meeting the quality parameters



Abbreviations

AWC	Aanganwadi Centre
FHTC	Functional Household Tap Connection
Gol	Government of India
GP	Gram Panchayat
HF	Health Facility
HH	Household
HGJ	Har Ghar Jal
JJM	Jal Jeevan Mission
LPCD	Litres per Capita per Day
MVS	Multi-village Scheme
NJJM	National Jal Jeevan Mission
RC	Residual Chlorine
O&M	Operation and Maintenance
OHT	Over Head Tank
PSU	Primary Sampling Unit
PWS	Piped Water Supply
SVS	Single Village Scheme
VAP	Village Action Plan
VWSC	Village Water and Sanitation Committee
WQMIS	Water Quality Monitoring and Information System



Glossary

- 1. Community Group of people living in one particular area or village/habitation
- Cross-sectional research A cross-sectional study is a type of research design in which data is collected from a relatively large and diverse group of people at a single point in time
- 3. **Drinking water source** Groundwater (open well, borewell, tube well, handpump, spring, etc.)/ surface water (river, lake, pond, reservoir, etc.)/rainwater, available for drinking and domestic use
- 4. Improved sources The following sources as considered improved by the National Family Health Survey definitions: Piped water into dwelling, yard/plot with a tap, piped water connected to public stand-posts, tube well or borewell, Hand pump, dug well– protected, Spring–protected, Rainwater, Water ATM/ Community RO plant/ Community Water Purification Plant (CWPP)
- 5. **Unimproved sources** The following sources as considered unimproved by the National Family Health Survey definitions: Unprotected spring, unprotected dug well, cart with small tank / drum, Tanker/ truck, Surface water (river/ dam/ lake/ pond/ canal), and bottled water
- 6. **Functional Household Tap Connection (FHTC)** A tap connection to a rural household for providing drinking water in adequate quantity of prescribed quality on regular basis.
- 7. **Functionality of FHTC** Functionality of a tap connection is defined as having infrastructure, i.e., household tap connection providing water in adequate quantity, as presented:

Definitions	Fully-functional	Partially-functional	Non-functional
Quantity	>= 55 LPCD	> 40 lpcd - < 55 LPCD	< 40 LPCD
Regularity	12 months or daily basis	9-12 months or < daily basis	< 9 months or < daily basis
Quality	Potable	Potable	Non potable

- 8. **Quantity (in litres)** of water received by households per person per day should meet the service level of 55 LPCD.
- 9. **Functionality Assessment** An assessment of the functionality of rural household tap connections based on a sample survey
- 10. **Regularity –** Regularity of water is considered when a rural household receives water for 12 months or on daily basis.
- 11. **Potability –** Potable water is water that is safe to be used as drinking water. Parameters of potable water are mentioned below:

	meters for potable water ed in the survey	Unit	Acceptable Limit	Permissible Limit in the absence of alternative sources
i.	pH (tested on site)	-	6.5 to 8.5	No relaxation
ii.	Free residual chlorine (tested on site)	Mg/litre	0.2	1
iii.	Turbidity	NTU	1	5
iv.	Total hardness	Mg/litre	200	600
٧.	Total alkalinity	Mg/litre	200	600
vi.	Chloride	Mg/litre	250	1000
vii.	Ammonia	Mg/litre	0.5	No relaxation
viii.	Phosphate	Mg/litre	0.3	1
ix.	Iron (in hotspots only)	Mg/litre	1	No relaxation
х.	Nitrate	Mg/litre	45	No relaxation
xi.	Sulphate	Mg/litre	200	400
xii.	Total dissolved solids	Mg/litre	500	2000
xiii.	Fluoride	Mg/litre	1	1.5



xiv.	Arsenic (in hotspots only)	Mg/litre	0.01	No relaxation
XV.	Bacteriological test for Total bacteria and E. coli or therm coliform bacteria		Shall not be detectable in any	100 ml sample

- 12. **Sampling** Selection of a subset of individuals from within a statistical population to estimate water service delivery among the population. In the current study, households have been sampled to estimate the representation of the village and subsequently of the district as well as of the state.
- 13. Types of schemes: Following are the piped water supply schemes that were assessed
 - a. Mini-solar based piped water supply scheme in isolated/tribal hamlets
 - b. Single Village Scheme (SVS) in villages having adequate groundwater that needs treatment
 - c. Single village scheme (having adequate groundwater/ spring water/ local or surface water source of prescribed Quality)
 - Retrofitting of ongoing schemes taken up under erstwhile NRDWP for the last mile connectivity/ retrofitting of completed rural water supply schemes to make it JJM compliant
 - e. Multi-village PWS scheme with water grids/ regional water supply schemes
- 14. Village Action Plan (VAP) Plan prepared by Gram Panchayat and/ or its sub-committee, i.e., VWSC/ Paani Samiti/ User Group, etc. based on baseline survey, resource mapping and felt needs of the village community to provide FHTC to every rural household, treat the generated greywater and plan its reuse, undertake surveillance activities, etc. VAP also indicates the fund requirement and timelines for completion of work under the Mission and will be approved by the Gram Sabha. Irrespective of the source of funding, all drinking water-related works in the village are taken up based on the VAP.
- 15. **Source Sustainability** includes measures such as aquifer recharge, rainwater harvesting, increased storage capacity of water bodies, reservoirs, de-silting, etc. improve the lifespan of water supply systems
- 16. Har Ghar Jal (HGJ) An administrative unit wherein all HHs are provided with water supply through FHTCs is called "Har Ghar Jal".
- 17. **Public Institutions** The public institutions in the survey include Aanganwadi Centre (AWC), Health Facilities, Schools, Gram Panchayat, and government buildings.
- 18. Working tap connection A tap connection supplied water at least one day in the week, preceding of survey
- **19. Functional Scheme –** A scheme is said to be functional if it was reported to be working for all 12 months in a year.



1. Factsheet

Table 1: District level factsheet

	Karnataka	Shivamogga
Functionality status of FHTC at households		
Households (HHs) which received water through FHTC at least	99	91
once in last 7 days (%)		
Fully functional (%)	59	70
Partially functional (%)	30	20
Non-functional (%)	12	10
Quantity of water received by households		
Adequate quantity (>55 LPCD) (%)	82	80
Partially adequate quantity (> 40 LPCD - < 55 LPCD) (%)	7	10
Inadequate quantity (<40 LPCD) (%)	11	10
Regularity of water received by households		
Fully Regular Supply (as per schedule) (%)	84	100
Partially Regular Supply (not as per schedule) (%)	13	0
Irregular Supply (less than 9 months' supply) (%)	3	0
Potable (Quality) water received by households		
Potable (%)	82	89
Non-potable (%)	18	11
Residual Chlorine (RCL) detected with in permissible limits (%)	32	2
Household level indicators		
Households receiving water supply daily-7 days a w	eek (%) 5	63 63
Daily HH requirement of water being met by FH	HTC (%) 9	94 100
Households reported FHTC as a primary source of drinking wa	ater (%) 6	SO 87
Households purifying water before drink	king (%) 7	72 50
Households paying water service delivery charge	ges (%) 6	67 94
Households having coping mechanisms during scar	rcity (%) 3	34 5
Households aware of grievance redressal mechanism for re	eporting	99 100
problems with FH	HTC (%)	100
Households reported incidence of water-borne diseases in the last y	/ear (%)	0 0
Households reported a reduction in time and effort in collecting wa	ater (%) 9	91 80
Overall user satisfaction at the household level		
Regula	arity (%) 🛛 🤄	92 94
Overall qua	ality (%) 8	37 90




Indicators	Karnataka	Shivamogga
Village level indicators (based on village questionnaire)		
Schemes reported to be functional (%)	28	43
Villages with groundwater resource (%)	74	100
Villages having groundwater recharge structure ¹ (%)	5	0
Water supply and storage status in villages		
Average no. of times water is supplied in a day	1	1
Villages having OHT/ Sump for storage of water (%)	82	92
Water quality monitoring and surveillance in the villages		
Villages with Field Test Kits (%)	56	85
Villages in which bacteriological test was done in last 1 year by VWSC/ Pani Samiti (%)	42	62
Villages reported to have a mechanism for chlorination (%)	6	0
VWSC/Pani Samiti and PWS signage in villages		
Village reported having presence of VWSC/ Pani Samiti (%)	35	15
Villages in which VWSC/ Pani Samiti is responsible for Operation & Maintenance of PWS schemes (%)	16	8
Villages in which persons are trained to use Field Test Kits (%)	53	62
Villages in which signages about JJM were observed (%)	11	0
Operation and maintenance at village		
Villages levying water service delivery to households (%)	60	100
Convergence of JJM activities with other schemes in the villages (%)	5	0
Villages having skilled manpower for Operation & Maintenance of PWS schemes (%)	44	23
Community monitoring of water wastage in villages (%)	31	23

 $^{^{1}}$ Out of villages who reported to have groundwater source (N_v=13)

2. Context

Jal Jeevan Mission (JJM) was launched on the 15th of August 2019 with the objective to provide functional household tap connections (FHTCs) to all rural households.

Figure 1: Har Ghar Jal - Objective, Vision, & Outcome



In accordance with the overall objectives as specified in the Operational Guidelines for the implementation of the NJJM, Gol carried out a sample survey to assess the functionality of household tap connections. As part of this endeavour, NJJM, Gol engaged HTA Kantar Public to conduct the 'Functionality Assessment' of the household as well as public institution/ buildings such as schools, anganwadis, gram panchayat buildings, public health facilities, and wellness centers in all the rural districts for the fiscal year 2021-22.

2.1. District snapshot: Shivamogga

District Shivamogga of Karnataka has a population of 12,60,023. The district has 7 blocks. Out of 1539 villages in the district, 183 are SC dominated and 22 are ST dominated villages. The district lies in Southern Plateau and Hills Region, West Coast Plains and Hills region and receives an annual rainfall of 2,417.6mm.

Presented here are district level information collated from the DDWS-IMIS:

Figure 2: District IMIS Status & Map

IMIS status:

- 234 (15% of all) villages are Har Ghar Jal
- 1305 (85% of all) villages are Non-Har ghar Jal
- Non-SC/ST dominated district
- Non-JE/AES
- Yes, history of water contamination
- 1100 (71% of all) villages with PWS are more than 20 FHTC





2.2. FHTC Assessment Objectives


Figure 3: Objectives of Functionality of Tap Connections



2.3. Assessment Methodology

A cross-section research design has been used for this functionality assessment study. Quantitative data were collected from villages and households across all states/UTs using the CAPI (Computer Assisted Personal Interviewing) mode. The survey includes two components, village, and household.

Figure 4: Survey Components & Respondents



2.4. Sample Size

The sample size was calculated to provide estimates with a 95% confidence interval (CI) and 5% margin of error (MoE) after incorporating the correction factor for a finite population considering the total number of geographic units having FHTCs.

- Village sample is estimated to be representative at the state level
- HH sample estimated to be representative at the district level



- Number of Har Ghar Jal (HGJ) villages were proportionately sampled at the district level
- All PWS schemes (up to 4) were covered per village. Per scheme approximately 9 (3 each from the head, middle, and tail HHs) or 18 households (6 each from head, middle, and tail HHs) were sampled to achieve the desired sample at the district level.

2.5. Sampling Methodology


As per the design, all villages having a PWS scheme with 20 or more functional household tap connections were included in the sample frame. The probability proportionate to size (PPS) method was used for village selection in each district. The steps for random selection of villages using PPS are as presented:

Figure 5: Steps for Village Sampling



The key considerations for the village and household sampling were:


Figure 6: Sampling Considerations – Village & Households



The record of all district-wise village replacements is maintained and reported as part of the annexure.

2.6. Methodology for Water Quantity Measurement at Households

Figure 7: Steps for Measuring Flowrate from Supply-tap at HHs



The flow rate of the water supply was measured using a container with gradual markings (either 5 litres or 1 litre, based on the flow of the tap) and a stopwatch/timer-watch. The process followed is as described in Figure 7.

In the case of households where the FHTC is connected directly with the storage tank, the following steps were adopted to measure the quantity:

- Assessor first asked and recorded length, breadth, and height.
- Assessor dipped a 5 feet long rod, marked the level of the water table, and calculated the volume – length x breadth x-height of water.
- Next the assessor opened the valve of the connection and allowed the water to flow inside the storage for 10 minutes.
- After 10 mins, the valve was closed, and the assessor again dipped the rod and recorded the new height of the water inside the tank. Based on this new 'height' and the CAPI calculated the changed volume.
- The difference in the volume of water in 10 minutes divided by 10 provided the flow rate of the water supply per minute.


The water flow rate was not measured for village-level public institutions.

2.7. Methodology for Water Quality Measurement

Water quality was tested for all public institutions available in the villages, including schools, anganwadis, gram panchayat buildings, public health facilities, and wellness centers, and at the selected households. Two types of quality tests were carried out – a) spot test for pH and free residual chlorine, and b) water sample was collected and transported to labs for testing against 13 quality parameters (total 15) as specified in Figure 8.



Figure 8: On-site & Laboratory Based Quality Test



JJM, with the support of the BMI Division of ICMR, enabled a new interface on the WQMIS portal for "Functionality Assessment (FA) User" to enable seamless harmonization of water sample registration, sample submission for testing, and sharing of results as per the applicable quality parameters.

2.8. Project implementation

An overview of the project implementation is as presented:




Figure 9: Broad project implementation framework

A total of 9 teams (comprising 9 supervisors, 54 assessors, and 9 water collection assistants) were recruited, trained, and deployed to complete the survey across the state of Karnataka. One survey team covered approximately 2 - 3 districts. The state-wise team deployment and fieldwork dates were as presented:

Table No. 1: State-wise team deployment and data collection start & end dates					tes
State		Teams deployed	Start date	End date	Total data collection days
Karnataka		9 Teams	2/17/2022	4/15/2022	55 Days

A four-tier quality control (QC) system was put in place. At the ground level, the data collection exercise was done using a computer-aided Personal Interview (CAPI) application which contained all logic and skip-checks inbuilt. Also, 5% of the total samples were accompanied by the supervisors. Sub-targeted QC was done by the state field managers (5%) and the central project management team (5%). Apart from this, the central research team monitored the data trend and as per requirement debriefed data collection teams to improve quality.

2.9. Sample coverage

Table No. 1: Sample covered						
	Targeteo	d sample	Achieved sample			
District	Village	НН	Village	НН	Public Institutions	
Shivamogga	13	378	13	384	0	
Karnataka	389	11,619	389	11,770	443	

2.10. Sampled village and household profile

SAMPLED VILLAGES	SAMPLED HOUSEHOLDS
Total no. of villages covered in the district – 13	Total no. of households covered in the district
Percentage of SC dominated villages covered	- 348
in the district is 15% (which is slightly higher	 Proportion of General - 45%, SC 26%, ST%
than the state average, i.e., 14%)	11, OBC 17% households
Percentage of ST dominated villages covered	44% of the FHTC connections are under the
in the district is 8% (which is slightly higher	name of a female member
than the state average, i.e., 6%)	 Average household size – 5
 Higher proportion of other (specify) 	 >75% positive user experience in 5/5
interviewed at the village level	measures
• Yes, the district reported to have any historical	
incidence of water contamination	



3. Findings

3.1. Functionality status of FHTC at household level

A. Overall Functionality* (in %)



Figure 10: Functionality of HH tap connection

It has been found that 91 percent of the sampled HHs (N=348) had working tap connections (i.e., received water at least once in last 7 days). Equal to seven out of ten (70 percent) HHs had fully functional tap connection (i.e., HHs receiving adequate quantity of prescribed quality of water on a regular basis).


3.2. Quantity, Regularity, and Quality of Water

Under JJM, functionality is defined as having infrastructure, i.e., household tap connection providing water in adequate quantity (55 LPCD or more) of prescribed quality on regular basis (every day or as decided by GP and/ or its sub-committee) with adequate pressure. It will also include long-term source and system sustainability. Presented here are the findings in this respect.

A. Water quantity measured as LPCD (Litres per Capita per Day)


80% HHs reported receiving adequate quantity of water

Figure 11: Quantity of water received by households




Quantity of water received across head, middle, and tail end HHs

Figure 12: Quantity of water received across head, middle and tail end households




B. Regularity of water supply to households

100% HHs receive a regular supply of water (as per agreed schedule) *Figure: Regularity of water received by households*




Regularity of water received across head, middle, and tail end

Figure 13: Regularity of water received across head, middle and tail end households



C. Water quality – Potability

Figure 14: Potable water received by households



*Potable water has been considered basis testing of water samples through laboratory tests for physical, chemical, and bacteriological as given in Table 4 parameters (within acceptable/permissible range) and onsite testing of pH. The details of laboratory test are mentioned in the table given above in the glossary.

Village quality parameters reported within permissible range (in %)

"No public institutes were found in any of the villages within the district."

Quality Parameters	No of samples tested	% Households	
pH (on-site)	348	89	
Turbidity	302	100	
Total Hardness	301	100	
Total Alkalinity	302	100	
Chloride	302	100	
Ammonia	Not Tested		
Iron	300	100	
Nitrate	301	100	
Sulphate	301	100	
Total Dissolved Solids	302	100	
Bacteriological Test(Presence/Absence)	Not Teste	ed	
Fluoride	302	100	
Arsenic	No histor	У	

Table No. 3:	Household water quality parameters reported within permissible range (in %
sample wi	ithin permissible range)

Safeguarding piped water supply for unforeseen bacteriological contamination-Presence of Residual Chlorine (RC)

The Residual Chlorine (RC) in the Karnataka was found in 5.0% samples. Out of which none of the samples were having RC outside range whereas 95% samples, had no RC. It may be mentioned that 100% of water samples passed the bacteriological contamination test but to assure the protection against bacteriological contamination, addition of RC is must in PWS system.

The Residual Chlorine in piped water supply is one of the most important preventive actions to assure quality of water against bacteriological contamination from source to consumption. The presence of residual chlorine within permissible limits is indicator of well-maintained and healthy piped water supply system.

It is advised that behavioural change communication campaigns on appropriate dosage of residual chlorine is held in all villages and monitoring system for chlorine dosing is established. The FTK must have residual chlorine testing facility for effective WQM&S.

Comment on functioning of District Lab:


The district lab tested water samples for 10 water quality parameters. 348 water samples were submitted, and 304 water samples were tested, and reports made available. The turnaround time for testing was more than 48 hours in most cases.

The labs did not have capacity to test more than 20-30 number of samples and had issues of human resource, regents etc.




3.3. Average water supply days in a week





3.4. Household utilization of water for drinking and other activities





Primary source of drinking water


primary source of drinking water

source of drinking water.

87% HHs reported HH tap connection as their

Figure 18: Households reported FHTC as primary

3.5. Status at HH level (Nh=384)



*HHs who reported complaints in last 1 year




3.6. Source sustainability at the village level

Schemes based on surface and ground water

8% of schemes are reported to be based on surface water and 77% ground water.


Figure 19: Schemes based on water source in village




*'Surface Water Source' is Stream, Spring, Glacier, River, lake, pond etc. and Groundwater Source is open well, borewell, tube well, handpump, spring, etc

Villages reported having presence of a groundwater source


100% of villages reported the presence of groundwater sources like improved dug wells and borewells, and none were supported by recharging structures.





The top 3 other source sustainability measure taken by villages

Figure 21: Villages reported having taken other source sustainability measure




% of villages

N_v = 13



3.7. Water quality monitoring and surveillance in the villages





3.8. Status of JJM

A. VWSC/Pani Samiti and PWS signage in villages ($N_v=13$)

Presence of VWSC/Pani	responsible for O&M of	responsible for O&M of	% Villages in which %	
Samiti	PWS Schemes	PWS Schemes	Villages – VWSC/PO	
15%	8%	62%	0%	

B. Water supply, storage and operation & maintenance at village level (Nv=13)

Average no. of supply in a day	% Villages levying water service delivery to HH	% Villages having skilled manpower for O&M for PWS	Community monitoring of water wastage in villages	
1	100%	23%	None%	
% Villages having OHT/ Sump	% Villages with O&M challenges	Primary points for reporting grievances	Key problems for reporting grievances	
92%	0%	PHED	Pipeline leakage	




3.9 Perception of HHs on Outcome Indicators

a. Health


Incidence of water borne diseases at HH level in last one year as reported

Figure 23: Household reported incidence of water borne diseases in last one year




b. Economic Income Change in employment days since FHTC programs/schemes

Figure 24: Household reported a change in employment days since FHTC programmes /schemes



c. Drudgery Reduction in time and effort in collecting water

Figure 25: Households reported reduction in time and effort in collecting water





3.9 User satisfaction

Table.No	Table.No.4: User satisfaction - more than 75% happy with FHTC services .						
S. No.	Parameter (Nh=384) In %						
1	Regularity		94				
2	Overall quality	0	90				
3	Colour	() ()	95				
4	Taste	() ()	95				
5	Odour	() ()	97				

Note:

Base (N_v)=13 means all villages sampled and covered in Shivamogga district

Base (N_H)=384 means all households sampled and covered across the 13 villages in Shivamogga district

Base (N_H)=384 means all households where female members used to fetch water before HH tap connection



4. Annexures

4.1. Summary of villages

Table N	Table No. 4: Village Summary						
S.No.	Name of sample village	Total HHs	Sample HHs	Actual sample HHs (achieved)	No. of scheme	No of source of surface water	No of source of Ground water
1	Total	29132	378	397	12		39
2	Donabaghatta	11157	36	37	1		4
3	Diggenahalli	416	9	11	1		2
4	Gangoor	595	27	28	1		1
5	Nagodi	3206	36	37	1		3
6	Siruvante	1310	27	28	1		1
7	Brahmanamanchale	1016	36	37	1		4
8	Kalmane	2310	36	37	1		4
9	Arenakoppa	825	18	20	1		3
10	Sogane	1895	36	38	1		2
11	Shakuvahalli	3035	36	38	1		5
12	Puttanahalli	855	18	20	0		2
13	Kanagalak	683	36	37	1		4
14	Sadashiva Pura	1829	27	29	1		4

4.2. Functionality – 55 LPCD vs regularity vs potability vs working tap connection

Table	Table No. 6: Functionality of HH tap connection							
S. No.	Village	Fully Functional* (% HH)	Adequate Quantity (% HH)	Fully Regular Supply (% HH)	Potable (Quality) (% HH)	Working tap connections (%HH)		
1	Total	69.8	79.6	100.0	88.8	100.0		
2	Donabaghatta	19.4	19.4	100.0	100.0	100.0		
3	Diggenahalli	0.0	100.0	100.0	0.0	100.0		
4	Gangoor	100.0	100.0	100.0	100.0	100.0		
5	Nagodi	22.2	83.3	100.0	25.0	100.0		
6	Siruvante	92.6	92.6	100.0	100.0	100.0		
7	Kalmane	97.2	97.2	100.0	100.0	100.0		
8	Arenakoppa	57.9	57.9	100.0	100.0	100.0		
9	Sogane	94.6	94.6	100.0	100.0	100.0		
10	Shakuvahalli	91.9	91.9	100.0	100.0	100.0		
11	Puttanahalli	94.7	100.0	100.0	94.7	100.0		
12	Kanagalak	47.2	47.2	100.0	100.0	100.0		
13	Sadashiva Pura	92.9	96.4	100.0	96.4	100.0		

* Fully Functional has been computed as = Adequate Quantity \cap Fully Regularity Supply \cap Potable (Quality)"



4.3. Villages not meeting the quality parameters

1. pH		Range- 6.5 to 8.5)	sfied at village I		
S.No.	Block Name	Panchayat Name	Villages	No. of HHs outside the acceptab	le range
1	Bhadravati	Sydarakallahalli	Diggenahalli		10
2	Hosanagara	Nitturu	Nagodi		27
2. Fre	ee residual chl	orine (Acceptable	Range- 0.2 to 1	PPM)	
S.No.	Block Name	Panchayat Name	Villages	HHs outside the acceptable/permissible range	HHs with no chlorine
1	Bhadravati	Dodderi	Gangoor	0	27
2		Donabagatta	Donabaghatta	0	36
3		Sydarakallahalli	Diggenahalli	0	10
4	Hosanagara	Nitturu	Nagodi	0	36
5	Sagar	Siruvante	Siruvante	0	27
6	Shikarpur	Kalmane	Kalmane	0	36
7	Shivamogga	B.Beeranahalli	Sadashiva Pura	0	20
8		Harnahalli	Arenakoppa	0	19
0 9		Sogane	Sogane	0	37
9 10	Soraba	Dyavanahalli	Puttanahalli	0	19
10	Sulaba	Shakunavalli	Shakuvahalli	0	37
12	Tirthahalli			0	36
		Mandagadde table Range- 1 to s	Kanagalak 5 NTU)	0	30
S.No.	Block Name	Panchayat Name	Villages	HHs outside the acceptable/permis	sible range
NA	NA	NA	NA	NA	
		Acceptable Range			
	Block	Panchayat			
S.No.	Name	Name	Villages	HHs outside the acceptable/permiss	sible range
NA	NA	NA	NA	NA	
		Acceptable Range-			
S.No.	Block Name	Panchayat Name	Villages	HHs outside the acceptable/permis	sible range
NA	NA	NA	NA	NA	
	loride (Accept	able Range- 250 to		/litre)	
S.No.	Block Name	Panchayat Name	Villages	HHs outside the acceptable/permise	sible range
NA	NA	NA	NA	NA	
		otable Range- 0.5		1	
	Block	Panchayat			
S.No.	Name	Name	Villages	HHs outside the acceptable/permiss	sible range
NA	NA	NA	NA	NA	
	n (Acceptable	Range- 1 Milligran	n/litre)		
S.No.	Block	Panchayat	Villages	HHs outside the acceptable/permiss	sible range
NA	Name	Name	_	· · ·	0.5
	NA ato (Accontabl	NA Rango 1 Milligr	NA m/litro)	NA	
	Block	e Range- 1 Milligra			
S.No.	Name	Name	Villages	HHs outside the acceptable/permise	v
	Shivamogga	B.Beeranahalli	Sadashiva Pura		1
1			o 400 Milligram/	litre)	
	Iphate (Accep	table Range- 200 t	o too miningranii		
10. Su	Block	Panchayat	Villages	HHs outside the acceptable/permis	sible range
10. Su S.No.		Panchayat Name	Villages		sible range
10. Su S.No. NA	Block Name NA	Panchayat Name NA	Villages NA	HHs outside the acceptable/permiss NA 000 Milligram/litre)	sible range



NA	NA	NA	NA	NA				
12. Ba	12. Bacteriological test (Presence)							
S.No.	Block Name	Panchayat Name	Villages	HHs outside the acceptable/permissible range				
NA	NA	NA	NA	NA				
13. Flu	13. Fluoride (Acceptable Range- 1 to 1.5 Milligram /litre)							
S.No.	Block Name	Panchayat Name	Villages	HHs outside the acceptable/permissible range				
1	Soraba	Dyavanahalli	Puttanahalli	1				
14. Ar	14. Arsenic (in hotspots) (Acceptable Range- 0.01 Milligram /litre)							
S.No.	Block Name	Panchayat Name	Villages	HHs outside the acceptable/permissible range				
NA	NA	NA	NA	NA				

